

IN THE CLAIMS

Please amend claim 12 as follows:

Claims 1 thru 10. (Canceled)

1 11. (Previously Presented) A unit for interconnecting a bar of soap and other items,
2 comprising:
3 a support body buried in the bar of soap;
4 first connecting means extending out of the bar of soap from a first end of the bar of
5 soap for connecting the bar of soap to a hanging device from which the bar of soap hangs;
6 and
7 second connecting means extending out of the bar of soap from a second end of the
8 bar of soap for connecting the bar of soap to one of the other items.

1 12. (Currently Amended) ~~[[The]] A unit of claim 11,~~ for interconnecting a bar of
2 soap and other items, comprising:
3 a support body buried in the bar of soap;
4 first connecting means extending out of the bar of soap from a first end of the bar of
5 soap for connecting the bar of soap to a hanging device from which the bar of soap hangs;
6 and
7 second connecting means extending out of the bar of soap from a second end of the

8 bar of soap for connecting the bar of soap to one of the other items;

9 wherein said first connecting means comprises an insertion shaft which is enlarged
10 at its end for insertion into a socket type clip provided at an end of the hanging device.

1 13. (Previously Presented) The unit of claim 12, wherein said second connecting
2 means comprises a shaft having a socket type clip formed on an end of said shaft for
3 connection to an enlarged end of an insertion shaft extending from one of the other items.

1 14. (Previously Presented) The unit of claim 11, wherein said second connecting
2 means comprises a shaft having a socket type clip formed on an end of said shaft for
3 connection to an enlarged end of an insertion shaft extending from one of the other items.

1 15. (Previously Presented) The unit of claim 11, wherein said first connecting means
2 comprises a shaft having a hook disposed on an end of said shaft for connection to the
3 hanging device.

1 16. (Previously Presented) The unit of claim 15, wherein said second connecting
2 means comprises a shaft having a ring formed at an end of said shaft for connection to a hook
3 formed on an end of a further shaft extending from one of the other items.

1 17. (Previously Presented) The unit of claim 11, wherein said second connecting

2 means comprises a shaft having a ring formed at an end of said shaft for connection to a hook
3 formed on an end of a further shaft extending from one of the other items.

1 18. (Previously Presented) The unit of claim 11, wherein said first connecting means
2 comprises a shaft having a bolt formed on an end of said shaft for connection to a nut part
3 formed on an end of the hanging device.

1 19. (Previously Presented) The unit of claim 18, wherein said second connecting
2 means comprises a shaft having a nut part formed on an end of said shaft for connection to
3 a bolt formed on an end of a further shaft extending from one of the other items.

1 20. (Previously Presented) The unit of claim 11, wherein said second connecting
2 means comprises a shaft having a nut part formed on an end of said shaft for connection to
3 a bolt formed on an end of a further shaft extending from one of the other items.

1 21. (Withdrawn) The unit of claim 11, wherein said support body comprises a
2 receptacle for holding a liquid within the bar of soap, and said second connecting means
3 includes a hollow shaft extending from said receptacle to said second end of the bar of soap,
4 and a stopper for stopping flow of the liquid from said receptacle and said hollow shaft at
5 said second end of the bar of soap.

1 22. (Withdrawn) The unit of claim 21, wherein said stopper is enlarged at an end
2 remote from the receptacle to form a support on which the bar of soap can sit when not in
3 use.

1 23. (Withdrawn) A unit for containing liquid within and dispensing liquid from a bar
2 of soap, comprising:
3 a receptacle buried in the bar of soap for holding the liquid;
4 a hollow shaft extending from said receptacle to an end of the bar of soap; and
5 a stopper insertable into the hollow shaft at the end of the bar of soap for retaining the
6 liquid in the bar of soap, and removable from the hollow shaft at the end of the bar of soap
7 for permitting removal of the liquid from the bar of soap.

1 24. (Withdrawn) The unit of claim 23, wherein said stopper is enlarged at an end
2 remote from the receptacle to form a support on which the bar of soap can sit when not in
3 use.

1 25. (Withdrawn) The unit of claim 23, further comprising first connecting means
2 extending out of the bar of soap from a first end of the bar of soap for connecting the bar of
3 soap to a hanging device from which the bar of soap hangs.

1 26. (Withdrawn) The unit of claim 25, further comprising second connecting means

2 extending out of the bar of soap from a second end of the bar of soap for connecting the bar
3 of soap to another item.

1 27. (Withdrawn) The unit of claim 23, further comprising connecting means
2 extending out of the bar of soap from a second end of the bar of soap for connecting the bar
3 of soap to another item.

1 28. (Withdrawn) The unit of claim 24, further comprising first connecting means
2 extending out of the bar of soap from a first end of the bar of soap for connecting the bar of
3 soap to a hanging device from which the bar of soap hangs.

1 29. (Withdrawn) The unit of claim 28, further comprising second connecting means
2 extending out of the bar of soap from a second end of the bar of soap for connecting the bar
3 of soap to another item.

1 30. (Withdrawn) The unit of claim 24, further comprising connecting means
2 extending out of the bar of soap from a second end of the bar of soap for connecting the bar
3 of soap to another item.